



UL Online Certifications Directory

ZPMV2.E146514

Wiring, Printed - Component

BASELECTRON SRL

E146514

VIA EINAUDI 7


27020 TRAVACO' SICCOMARIO, PV ITALY

	Cond Width		Cond	SS/	Max Area	Solder		Max Oper	Meets	C	
	Min	Edge				Thk	Diam				Limits
Type	mm(in)	mm(in)	mic(mil)	DS	mm(in)	C	sec	C	Class	DSR	I
Multi-layer printed wiring boards.											
B_2	0.14 (0.006)	0.14 (0.006)	17 (0.67) Int: 68	DS	25.4 (1.0)	288	10	130	V-0	All	-
Multilayer printed wiring boards.											
B	0.08 (0.003)	0.08 (0.003)	16.5 (0.65) Int:66	DS	50.8 (2.0)	275	10	125	V-0	All	*
B-2	0.09 (0.004)	0.27 (0.011)	17 (0.67)	DS	25.4 (1.0)	280	20	130	V-0	All	-
B2	0.11 (0.004)	0.18 (0.007)	17 (0.67) Int: 34	DS	25.4 (1.0)	280	20	130	V-0	All	-
Single layer printed wiring boards.											
A	0.08 (0.003)	0.08 (0.003)	16.5 (0.65)	DS	50.8 (2.0)	275	10	125	V-0	All	*
A-2	0.09 (0.004)	0.27 (0.011)	16.5 (0.65) Int:34	DS	25.4 (1.0)	280	20	130	V-0	All	-
A2	0.11 (0.004)	0.18 (0.007)	17 (0.67)	DS	25.4 (1.0)	280	20	130	V-0	All	-
A_2	0.14 (0.006)	0.14 (0.006)	17 (0.67)	DS	25.4 (1.0)	288	10	130	V-0	All	-

* - CTI PLC is marked on individual board.

DS - Duoble-Sided

NOTE - A triangle is marked on those products within a given type designation that comply with direct support of current-carrying parts performance level requirements of UL 796. "All" is used to indicate that all base materials under that type designation comply with direct support of current-carrying parts performance level requirement of UL796.

Marking: Company name or trademark  and type designation. May be followed by a suffix to denote factory identification.

[Last Updated](#) on 2007-10-30